

FS-3040MFP/FS-3140MFP

MONOCHROME MULTIFUNCTIONALS FOR A4 FORMAT

▶ print ▶ copy ▶ scan ▶ fax

MADE FOR **LOW-COST** **HIGH-VOLUME** DOCUMENT OUTPUT.

Made for dynamic work groups with the highest demands in productivity, these MFPs have a short first copy time, deliver their output at a fast 40 ppm and scan at an impressive rate of 35 ipm. And with a paper capacity of up to 2,100 sheets, a smooth workflow is guaranteed. The long-life components provide exceptional reliability and unbelievably low running costs, while keeping environmental impact at an absolute minimum. Perfect for your office.

- ▶ Up to 40 pages per minute in A4
- ▶ First copy time of 7 seconds
- ▶ High resolution of 1,200 dpi
- ▶ Standard print, copy, colour scan and fax* functionality
- ▶ Standard duplex unit for cost-saving double-sided printing
- ▶ Standard reverse automatic document processor
- ▶ Up to three optional paper feeders for up to 2,100 sheets
- ▶ LDAP support, IPsec and SSL encryption
- ▶ Exceptionally low output costs in its class

*only FS-3140MFP

All scanned documents can be sent directly to any folder, PC, USB host or mail account on your network – encoded for full security.



Enhanced security features such as IPsec, SSL and LDAP support are standard.



Ecosys

 **KYOCERA**

FS-3040MFP/FS-3140MFP

MONOCHROME MULTIFUNCTIONALS FOR A4 FORMAT

ECOSYS stands for **ECO**logy,
ECONomy and **SYSTEM**-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center

The Status Monitor shows the current printer's condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

General

Technology: KYOCERA ECOSYS Laser, Mono component
Engine speed: Up to 40 pages A4 per minute
Resolution: 1,200 x 1,200 dpi (print), 600 x 600 dpi, 256 greyscales (scan/copy)
Duty cycle: Max. 200,000 pages per month
Recommended monthly printing volume: up to 8,000 pages**
Warm-up time: Approx. 22 seconds or less
Time to first print: Approx. 9.5 seconds or less
Time to first copy: Approx. 7 seconds
CPU: PowerPC 440/667 MHz
Memory: Standard 256 MB (2 x 128 MB DIMM), max. 768 MB (256 MB + 512 MB DIMM)
Standard interface: USB 2.0 (Hi-Speed), USB Host, Fast Ethernet 10/100Base-TX standard, slot for optional internal print server (FS-3040MFP only)
Integrated accounting: 20 department codes
Dimensions (W x D x H): 494 x 497.1 x 545.5 mm
Weight: Approx. 25.5 kg (FS-3040MFP), approx. 25.8 kg (FS-3140MFP)
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
Copying/Printing 3in1: 676.6 W; 4in1: 677.4 W
Stand-by 3in1: 95.8 W; 4in1: 97.9 W
Sleep-mode 3in1: 6.9 W; 4in1: 10.6 W
Noise (ISO 7779/ISO 9296):
Copying/Printing: 55 dB(A)
Stand-by: 30 dB(A)
Safety standards: TÜV/GS, CE
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: Max. 100-sheet multi-purpose tray, 60-220 g/m², (70 x 148 to 216 x 356 mm)
Max. 500-sheet universal paper cassette, 60-120 g/m²; custom (105 x 148 to 216 x 356 mm), max. input capacity with options: 2,100 sheets
Duplex unit: Duplex as standard supports 60-120 g/m²
Reversing document processor: 50-sheet, Simplex scan 50-120 g/m², Duplex scan 50-110 g/m², custom (140 x 210 to 216 x 356 mm)
Output capacity: Max. 500 sheets face-down

Your KYOCERA Business Partner:

Print functions

Controller language: PRESCRIBE IIe
Emulations: PCL6 (5e/XL), KPD L 3 (PostScript 3-compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PRESCRIBE, XPS, PDF Direct Print
Operating systems: All current Windows operating systems, MAC OS 9.X, MAC OS X, Linux
Fonts/barcodes: 93 outline fonts (PCL6, HP compatible) + 8 (Windows Vista), 101(KPDL3), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)
Features: PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3

Copy functions

Max. original size: A4/legal
Continuous copying: 1-999
Zoom range: 25-400% in 1% steps
Preset magnification ratios: 7 Reductions/5 Enlargements
Digital features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control
Exposure mode: Auto, manual: 7 steps
Image adjustments: Text + photo, text, photo

Scan functions

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, TWIN, WSD
Scan speed: 35 ipm (300 dpi, A4, b/w)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)
Max. scan size: A4, legal
Original recognition: Text, photo, text + photo OCR
Network protocol: TCP/IP, NetWare, AppleTalk, NetBEUI
File types: TIFF, PDF, JPEG, XPS
Compression method: MMR/JPEG
Features: Colour scan, integrated address book, LDAP support, encrypted data transfer, multi-send (e-mail, fax, SMB/FTP folder, print) at once

Fax functions (FS-3140MFP only)

Compatibility: ITU-T G3
Modem speed: Max. 33.6 kbps
Transmission speed: Less than 3 seconds
Scanning speed: 2.5 seconds

One touch dial: 22 numbers

Address book: 100 entries
Scanning density:
Normal: 8 dot/mm x 3.85 line/mm
Fine: 8 dot/mm x 7.7 line/mm
Superfine: 8 dot/mm x 15.4 line/mm
Ultrafine: 16 dot/mm x 15.4 line/mm
Maximum original size: A4, legal
Compression method: JBIG, MMR, MR, MH
Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

Options

Paper handling
PF-310 Paper feeder: Max. 500 sheets, 60-120 g/m², A4, B5, A5, letter, legal, custom (148 x 210 mm to 216 x 356 mm)
Memory upgrade: MDDR2-128: 128 MB; MDDR2-256: 256 MB; MDDR2-512: 512 MB
CompactFlash* card: CF-4 (4 GB) for printing forms, fonts, logos, macro storage
Others
USB Flash Memory: Supports direct printing of PDF, XPS, TIFF files via USB Host interface
Optional interfaces (FS-3040MFP only):
PS159: Wireless LAN (802.11b/g)
PS1109 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)
PS129 Fibre Optic: 100BaseSX (SC)
PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)
CB-310: High wooden desk with storage capacity, including castors (wheels)
CB-320: Low wooden desk with storage capacity, including castors (wheels)

Consumables

TK-350 Toner-Kit: Microfine toner for 15,000 pages in accordance with ISO /IEC 19752
Capacity of starter toner is 7,500 pages in accordance with ISO /IEC 19752

Warranty

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYO LIFE Up to 3-year on-site warranty extensions available for printer and options.



Product depicted includes optional extras.

KYOCERA MITA Belgium nv/sa, Sint-Martinusweg 199-201, 1930 Zaventem
Tel +32 (0)2 720 92 70 - Fax +32 (0)2 713 08 75
www.kyoceramita.be - info@kyoceramita.be

KYOCERA MITA Corporation - 2-28, 1-Chome - Tamatsukuri - Chuo-Ku
Osaka 540-8585 - Japan - www.kyoceramita.com

* KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. **Based on 36 months' usage

KYOCERA